

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC**1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product name OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC

Internal identification API GL 5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Gear oil

1.3. Details of the supplier of the safety data sheet

Company name Rchemie International Kimya San. Ve Tic. Ltd. Şti.

Address Tepeören İTOSB Mah. 8. Cad. No:10 Tuzla/İstanbul

Tel +90 216 504 61 77

Fax +90 216 504 61 79

E-mail www.olarlubricants.com

2. Hazards Identification**2.1. Classification of the substance or mixture**

Health hazards Xi – Irritant
R43 May cause sensitization by skin contact.

Environmental hazards Not classified

2.2. Label Elements

Hazard statements No Significant Hazard

3. Composition/information on ingredients**3.2. Mixtures**

SULPHURISED ISOBUTYLEN	270-943-2	1 - 10% R52/53
------------------------	-----------	----------------

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC

Long chain alkenyl amine	204-015-5	0 - 0.5% Acute Tox. 4: H302; Skin Corr. 1B: H314; Eye Dam. 1: H318; STOT SE 3: H335; STOT RE 2: H373; Aquatic Acute 1: H400;
--------------------------	-----------	--

4. First aid measures
4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations.
-----------------------------	------------------------------

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC**5. Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture**Specific hazards**

Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

5.3. Advice for firefighters**Protective actions during firefighting**

Avoid breathing fire gases or vapours. Fight fire from safe distance or protected location. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters

Use protective equipment appropriate for surrounding materials.

6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****Personal precautions**

For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions**Environmental precautions**

Do not discharge into drains or watercourses or onto the ground. Avoid or minimise the creation of any environmental contamination. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC

Methods for cleaning up

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

7. Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits No data available.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. Provide adequate ventilation.

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Other skin and body protection	Min.250 °C
Hygiene measures	Wash promptly if skin becomes contaminated. Promptly remove non-impervious clothing that becomes contaminated. When using do not drink or smoke. Contaminated clothing should be placed in a closed container for disposal or decontamination.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

9. Physical and Chemical Properties**9.1. Information on basic physical and chemical properties**

Appearance	Liquid.
Flash point	Min.220 °C
Bulk density	0,860 g/cm ³ @15°C (ASTM D 4052)
Viscosity	15,03 mm ² /s @ 100°C

9.2. Other information

Other information	Not available.
--------------------------	----------------

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC**10. Stability and reactivity****10.1. Reactivity**

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical Stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11. Toxicological information**11.1. Information on toxicological effects**

Germ cell mutagenicity

Genotoxicity - in vitro No information available.

Genotoxicity - in vivo No information available.

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity No information available.
- fertility

Reproductive toxicity – No information available.
development

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity
- repeated exposure

STOT – repeated No information available.
exposure

Inhalation No specific health hazards known.

Ingestion May cause discomfort if swallowed.

Skin contact Liquid may irritate skin.

Eye contact May cause temporary eye irritation.

12. Ecological Information

12.1. Toxicity No data available

12.2. Persistence and degradability

Persistence and There are no data on the degradability of this product.

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC

degradability**12.3. Bioaccumulative potential****Bioaccumulative potential** No data available on bioaccumulation.**12.4. Mobility in soil****Mobility** The product is partly miscible with water and may spread in the aquatic environment.**12.5. Results of PBT and vPvB assessment****Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.**12.6. Other adverse effects****Other adverse effects** No information required.

13. Disposal considerations**13.1. Waste treatment methods****General information** The packaging must be empty (drop-free when inverted).**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Environmental Manager must be informed of all major spillages.
Avoid the spillage or runoff entering drains, sewers or watercourses.

14. Transport information**14.1. General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID)**14.2. UN Number** Not applicable**14.3. UN proper shipping name** Not applicable

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC

14.4. Transport hazard class No transport warning sign required.

14.5. Packing group Not applicable

14.6. Environmental hazards

Environmentally
hazardous
substance/marine
pollutant No

14.7. Special precautions for user Not applicable.

14.8. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk
according to
Annex II of MARPOL 73/78
and the IBC Code Not applicable.

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

16. Other information

Key literature
references and
sources for data This SDS is prepared based on the information received from the
the product raw material.

OLAR GEGA EX-TEC SMT 75W90 GL-5 SEMI SYNTHETIC

Text of risk phrases	R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment Acute Tox. 4: H302 - Harmful if swallowed Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure Aquatic Acute 1: H400 - Very toxic to aquatic life.
-----------------------------	---

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.